**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claims 1 to 33. (Canceled).

34. (Previously Presented) A method for controlling at least one target device, comprising:

(a) obtaining a first address and a second address from a first device;

(b) providing the first and second addresses to a command device;

(c) providing a message, located at the first address to the first device using the command device; the message including the second address;

(d) transmitting the message, located at the first address, to a second device;

(e) extracting the second address from the message using the second device;

(f) storing the second address using a memory unit;

(g) providing a command signal and a data signal to the first device;

(h) transmitting the command signal, located at the second address, to the second device;

(i) controlling the at least one target device using the command signal;

(j) transmitting the data signal to the second device;

(k) providing the data signal to an output device by the second device; and

(l) providing, by the output device, an output as a function of the data signal while the at least one target device is controlled using the command signal.

35. (Original) The method according to claim 34, wherein the message includes a predetermined data of the command and data signals.

36. (Original) The method according to claim 35, wherein the at least one target device selects the command signal as a function of the predetermined data.

Claims 37 to 48. (Canceled).

49. (New) A communication and control system, comprising:

at least one target device;

a first device;

a command device configured to receive a first address and a second address obtained from the first device and provide a message to be provided at the first address to the first device, the message including the second address;

a memory unit configured to store the second address;

a second device configured to receive the message and extract the second address from the message, wherein:

the first device is provided with a data signal and a command signal, the command signal to be provided at the second address;

the data signal and the command signal are transmitted to the second device; and

the second device controls the at least one target device using the command signal; and

an output device configured to receive the data signal from the second device and provide an output as a function of the data signal while the at least one target device is controlled using the command signal.

50. (New) The system according to claim 49, wherein the message includes a predetermined data of the command and data signals.

51. (New) The method according to claim 50, wherein the at least one target device selects the command signal as a function of the predetermined data.

52. (New) A computer-readable storage medium storing a set of instructions, the set of instructions capable of being executed by a processor to implement a control operation of at least one target device on at least one computer system, the method comprising:

(a) obtaining a first address and a second address from a first device;

(b) providing the first and second addresses to a command device;

(c) providing a message, located at the first address to the first device using the command device, the message including the second address;

(d) transmitting the message, located at the first address, to a second device;

(e) extracting the second address from the message using the second device;

(f) storing the second address using a memory unit;

(g) providing a command signal and a data signal to the first device;

(h) transmitting the command signal, located at the second address, to the second device;

(i) controlling the at least one target device using the command signal;

(j) transmitting the data signal to the second device;

(k) providing the data signal to an output device by the second device; and

(l) providing, by the output device, an output as a function of the data signal while the at least one target device is controlled using the command signal.

53. (New) The computer-readable storage medium according to claim 52, wherein the message includes a predetermined data of the command and data signals.

54. (New) The computer-readable storage medium according to claim 53, wherein the at least one target device selects the command signal as a function of the predetermined data.